

ALLIANCE **AGRICULTURE**

TRA: I-1 Speed Rating: A8 Alliance 223 Implement is a heavy-duty tire designed to carry heavy loads under tough field conditions. The strong nylon construction and the all-around protection against ozone layer impact and sunlight ensure long tire life.

Fronts & Implements - 9.00-13

ı	Size	Rim	Unloaded Dimension			Rolling Circumference mm		Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
ı					Loaded Static					Speed									
ı					radius					Drive Wheel				Free rolling					
ı			SW mm	OD mm						10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph
ſ	9.00- 13	5.50 X 13		814		2310		8 119A8G+ 106BG+ 119A8G 106BG	0.8	645	549	516	461	415	924	785	739	660	594
					354				1.2	819	696	655	585	527	1172	996	937	837	753
			247						1.6	969	823	775	692	623	1387	1179	1110	991	892
			247						2	1103	938	883	788	709	1581	1344	1264	1129	1016
									2.4	1228	1044	982	877	789	1758	1495	1407	1256	1130
									2.75	1330	1131	1064	950	855	1904	1618	1523	1360	1224
1	Size	Rim	Unloaded Dimension			Loaded			Load Index PR Symbols			Recommended Load							
ı					on			Rolling		Inflation Pressure bar		Speed							
ı					St	atic radius mm	Circumference mm					Drive Wheel				Free Rolling			
ı			SW mn		OD mm								25 kmph	40 kmph	50 kmph	10 kmph	25 kmph	40 kmph	50 kmph
	9.00- 13	5.50F X 13		236	780				12	_ 2	2.9	1470	1250	1050	950	2090	1770	1490	1340
						354			123A8⊖+ 120B⊖+ 123A8⊖ 120B⊖	3	3.1	1530	1300	1090	980	2170	1840	1550	1400
			23				2310	2310		3	3.7	2190	1860	1560	1400	2600	2210	1860	1680

E-Marking Number:

