



**ALLIANCE
 AGRICULTURE**

TRA: **R-1**
 Speed Rating: **D**

TL
 TUBE LESS

The Alliance 350 is a special line of radial narrow tires for all types of cultivation, harvesting and spraying jobs. The tire is characterized by round shoulders for soil and crop protection. A tough casing and rigid belt provides all the advantages of radial construction. This tire is used as front wheel in Row Crop applications.

TRACTOR - 270/95R54(11.2R54) Steel Belted

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load							
		SW mm	OD mm					Speed							
								Non cyclic operation							
								Static kmph	10 kmph	15 kmph	25 kmph	40 kmph	50 kmph	65 kmph	70 kmph
270/95R54(11.2R54)	W9X54 W10X54	285	1900	901	5826	146D 149A8	0.8	2790	1820	1630	1440	1330	1280	1215	1110
							1.6	4490	2930	2610	2310	2140	2050	1950	1770
							2.4	5150	3360	3000	2650	2450	2350	2240	2040
							3.6	6440	4200	3750	3320	3070	2940	2800	2550
							4	6900	4500	4020	3560	3290	3150	3000	2730

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load	
		SW mm	OD mm					Speed	
								Cyclic operation	
								10 kmph	15 kmph
270/95R54(11.2R54)	W9X54 W10X54	285	1900	901	5826	146D 149A8	1	2070	1880
							2	3320	3020
							3	3810	3470
							4.5	4760	4340
							5	5100	4650

