



ALLIANCE
AGRICULTURE

TRA: I-3
Speed Rating: A8

Alliance 328 VALUE PLUS is specially designed for low end applications like balers,wagons and other agricultural implements.It displays excellent flotation and self cleaning characteristics.The tire has moderate traction flotation profile and provides maximum soil protection and low compaction.

Fronts & Implements - 300/80-15.3IMP(11.5/80-15.3IMP)

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load											
								Speed											
		SW mm	OD mm					Drive Wheel					Free Rolling						
								Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph	Static kmph	10 kmph	20 kmph	30 kmph	40 kmph	50 kmph
300/80-15.3IMP(11.5/80-15.3IMP)	9.00 X 15.3	292	855	375	2456	10 131A8⊕ 119A8⊕	0.8	1372	820	736	654	584	526	1370	1160	1046	930	830	747
							1.6	2059	1230	1104	981	876	788	2063	1750	1575	1400	1250	1125
							2.4	2609	1550	1399	1243	1110	999	2624	2230	2003	1781	1590	1431
							3.2	3086	1840	1654	1471	1313	1182	3102	2630	2369	2106	1880	1692
							3.4	3196	1900	1714	1523	1360	1224	3218	2730	2457	2184	1950	1755

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
								Speed									
		SW mm	OD mm					Drive Wheel					Free rolling				
								10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph
300/80-15.3(11.5/80-15.3) IMP	9.00X15.3	292	855	375	2456	10 A8⊕ ⊕ A8⊕ ⊕	0.8	816	694	653	583	520	1170	996	937	837	753
							1.2	1035	879	828	739	670	1490	1263	1188	1061	955
							1.6	1225	1041	980	875	788	1757	1493	1406	1255	1130
							2	1396	1186	1117	997	897	2002	1702	1602	1430	1287
							2.4	1553	1320	1242	1109	998	2227	1893	1782	1591	1432
							2.8	1700	1445	1360	1214	1093	2437	2072	1950	1741	1567
							3.2	1838	1562	1471	1313	1182	2635	2240	2108	1882	1694
							3.4	1904	1618	1523	1360	1224	2730	2321	2184	1950	1755

E-Marking Number:

