



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **D**

The Alliance 365 (High-Speed Drive Tractor Radial) tires are available in a complete range of front and rear combination tires. The tread patterns on these tires represent the trend of modern radial agricultural tires with a low aspect ratio. High tire volume along with low inflation pressure provides high traction and increased soil protection. The lug design ensures better self-cleaning with reduced tire slippage. Multi lug angle tread pattern and over-lapping central lugs ensure on & off-road suitability.

TRACTOR - 480/65R28

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
								Speed						
		Non Cyclic Operation												
		NaN kmph	Field kmph					10 kmph	25 kmph	40 kmph	50 kmph	65 kmph		
480/65R28	W15L X 28 W14L X 28	484	1335	624	4094	142D 145A8	0.8	1670	1670	2180	1720	1590	1520	1450
							1.6	2580	2580	3360	2650	2450	2350	2240
							2.4	3050	3050	3980	3140	2900	2780	2650
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
								Speed						
		Cyclic Operation												
		10 kmph	15 kmph											
480/65R28	W15L X 28 W14L X 28	484	1335	624	4094	142D 145A8	1	2470	2250					
							2	3810	3470					
							3	4510	4110					

* Alliance allows for free rolling application: Load capacity to be increased by 20%, after increasing the inflation pressure by 20%.

