



ALLIANCE  
AGRICULTURE  
  
TRA: **R-1W**  
Speed Rating: **D**

The Alliance 372 Agriflex+ Very High Flexion (VF) tires are designed with increased flexibility in the sidewall to enable the tire to carry up to 40% more load at the same pressure as a standard radial tire. They can also carry the same load as a standard radial tire with up to 40% less air pressure. This reduction in air pressure creates a bigger footprint for more traction, less slip, better fuel efficiency, and decreased soil compaction, resulting in more yield.

Harvester - VF 710/70R38 CFO

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
								Speed									
		SW mm	OD mm					CFO(hlc)		Road Transport							
										15 kmph	30 kmph	10 kmph	15 kmph	20 kmph	25 kmph	30 kmph	40 kmph
VF 710/70R38 CFO	DW25B X 38	720	1959	843	5735	178D	0.8	6440	5390	5230	4990	4940	4890	4850	4750	4750	4320
	DW24B X 38						1	7380	6190	6000	5720	5670	5610	5560	5450	5450	4960
	DW23B X 38						1.2	8330	6980	6770	6460	6400	6330	6270	6150	6150	5600
	DW23B X 38						1.4	9080	7600	7370	7040	6970	6900	6830	6700	6700	6100
	DW23B X 38						1.6	10160	8510	8250	7880	7800	7730	7650	7500	7500	6830

E-Marking Number:

