



ALLIANCE
AGRICULTURE

TRA: **R-1W**
Speed Rating: **D**

The Alliance 372 Agriflex+ Very High Flexion (VF) tires are designed with increased flexibility in the sidewall to enable the tire to carry up to 40% more load at the same pressure as a standard radial tire. They can also carry the same load as a standard radial tire with up to 40% less air pressure. This reduction in air pressure creates a bigger footprint for more traction, less slip, better fuel efficiency, and decreased soil compaction, resulting in more yield.

Harvester - VF710/60R30

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
								Speed				
		Non Cyclic Operation										
		SW mm	OD mm					10 kmph	15 kmph	20 kmph	25 kmph	70 kmph
VF710/60R30	DW25BX30	710	1615	696	4707	171D	0.8	3800	3550	3550	3550	3230
							1.2	4820	4500	4500	4500	4100
							1.6	5840	5450	5450	5450	4960
							2	6590	6150	6150	6150	5600
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load				
								Speed				
		Cyclic Operation										
		SW mm	OD mm					10 kmph				
VF710/60R30	DW25BX30	710	1615	696	4707	171D	1	4970				
							1.5	6300				
							2	7630				
							2.5	8610				

