




**ALLIANCE
 CONSTRUCTION &
 INDUSTRIAL**

TRA: **R-4**
 Speed Rating: **A8**



Alliance 570 is an ideal radial tire for industrial and construction services. The tread pattern enables strong grip and high traction performances on soft surfaces, as well as comfortable work on hard surfaces and stable running on the roads. The strong polyester construction enables higher vehicle speed as well as increased puncture protection. Flatter tread because of radial tire construction provides even pressure distribution, high productivity and optimal fuel consumption.

TRACTOR - 460/70R24(17.5LR24)

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
								Speed								
		Constant load						Cyclic Applications								
		SW mm	OD mm					Static kmph	10 kmph	30 kmph	40 kmph	50 kmph	10 kmph	30 kmph	40 kmph	50 kmph
460/70R24(17.5LR24)	W15L W14L	445	1245	564	3682	145A8 142B	1.5	4950	2690	2190	2150	2150	3230	2300	2150	2150
							2.2	6190	3360	2740	2690	2690	4040	2880	2690	2690
							2.5	6670	3630	2960	2900	2900	4350	3100	2900	2900
						150A8 147B	2.6	7080	3850	3140	3080	3080	4620	3300	3080	3080
							2.8	7410	4030	3280	3220	3220	4830	3450	3220	3220
							3	7710	4190	3420	3350	3350	5030	3580	3350	3350
							3.6	9450	5140	4400	4110	4110	6170	4400	4110	4110
						159A8 159B	3.8	9780	5310	4550	4250	4250	6380	4550	4250	4250
							4	10060	5470	4680	4375	4375	6560	4680	4375	4375

Note: For above mentioned size 145A8 is no longer active for production.

Note : This size is available without steel belts. Available in polyester construction only. Recommended rim in red. ^ One way distance 600 m.

