


**ALLIANCE  
CONSTRUCTION &  
INDUSTRIAL**

TRA:

Speed Rating: A8

Alliance 580 is built with a unique tread pattern that enables strong grip and high traction on soft surfaces, as well as work on hard surfaces. Its robust carcass construction contributes to the high stability of the machine, especially while working on sloppy terrains, and ensures complete puncture protection. Because of its central lug design, the tire is well suited for both on and off-road applications making it a good tire for multi-purpose transportation.

**Telehandler - 425/75R20(16.5R20)**

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
		Speed						Constant Load						Cyclic Application			
		Static	10 kmph	20 kmph	25 kmph	30 kmph	40 kmph	50 kmph	10 kmph	15 kmph							
425/75R20(16.5R20)	13 X 20	440	1137	512	3432												
Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load									
		Speed						Constant Load						Cyclic Application			
		Static	10 kmph	20 kmph	25 kmph	30 kmph	40 kmph	50 kmph	10 kmph	15 kmph							
425/75R20(16.5R20)	13 X 20 12 X 20 12SDC X 20 13SDC X 20 14 X 20	420	1138	509	3516	154A8 154B	1.2 1.6 2.4 3.2 4	3565 4370 5589 7073 8625	1938 2375 3038 3844 4688	1690 2071 2649 3352 4088	1643 2014 2576 3260 3975	1612 1976 2527 3198 3900	1550 1900 2430 3075 3750	1411 1729 2211 2798 3413	2325 2850 3645 4613 5625	2077 2546 3256 4121 5025	

