

**ALLIANCE
FORESTRY****TRA: LS-2****Speed Rating: A8****Warranty: 5 years**

344 Forestar is a steel-belted tire that provides high puncture resistance. Special tread compound along with thick sidewalls with under tread provides additional strength to the tire. The reinforced bead of the tire provides exceptional performance with extra bead protection. Its tread design and lug angle provide excellent grip. Wide inter-lug space helps in self-cleaning. The close spacing of the lugs in the center of the tire gives better stability & reduces rolling resistance.



Forwarder & Harvester - 650/45-24.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load						
								Speed						
		Forestry use						LOG SKIDDER APPLICATION						
		SW mm	OD mm					10*HT{* ht} Kmph	10*LT{* lt} Kmph	Static Kmph	10 Kmph	20 Kmph	30 Kmph	40 Kmph
650/45-24.5	AG22.00 X 24.5	640	1234	579	3720	20 161A8 168A2	3	3430	4220	7890	4800	4220	3670	3430
							4	4060	4990	9340	5680	4990	4340	4060
							4.5	4350	5350	10010	6090	5350	4650	4350
							5	4625	5690	10640	6480	5690	4950	4625