



ALLIANCE  
AGRICULTURE  
  
TRA:  
Speed Rating: **D**

Alliance 885 is specially engineered to carry high loads at high speeds for a wide variety of agri-transport applications. Its directional tread pattern provides superior traction and excellent self-cleaning. It has a steel belted construction that ensures lower downtime leading to lower maintenance cost and strong casing that provides higher wear resistance. The large footprint along with rounded shoulders provides crop protection and minimizes soil compaction making it an ideal agri-transport offering.

Fronts & Implements - 850/50R30.5

Size	Rim	Unloaded Dimension		Loaded Static radius mm	Rolling Circumference mm	Load Index PR Symbols	Inflation Pressure bar	Recommended Load								
								Speed								
		MIXED APPLICATION														
		Static kmph	10 kmph					25 kmph	30 kmph	40 kmph	50 kmph	60 kmph	65 kmph	70 kmph		
SW mm	OD mm															
850/50R30.5	AG28.00 X 30.5	862	1625	740	4933	182D	0.8	6268	4905	4306	4115	3706	3297	2916	2725	2480
							1.6	10063	7875	6913	6606	5950	5294	4681	4375	3981
							2.4	13340	10440	9164	8758	7888	7018	6206	5800	5278
							3.2	16330	12780	11218	10721	9656	8591	7597	7100	6461
							4	19550	15300	13430	12835	11560	10285	9095	8500	7735

E-Marking Number:

