



ALLIANCE FORESTRY

TRA: I-3 Speed Rating: A8/B



Alliance 328 Flotation tire is a specially designed tire constructed to carry heavy loads and is used in harsh conditions. It provides improved stability over dual-tire configuration. The tire also provides much better ride comfort, higher machine mobility, better self cleaning and better overall performances on road. 328 comes in Steel Belted, Fabric and Heavy Duty variants for different sizes. Test description.

## FORESTRY - 400/60-15.5 Steel Belted

Size			Unloaded Dimension									Speed										
		Rim				Loaded Static radius mm	Rolling Circumference		Load Index PR		Inflation Pressure		re	Constant load application								
										Symbols		Dai		Drive wheel					Forestry use			
			SW mm		DD mm										10 mph	20 kmph	30 kmph	40 kmph	10*HT kmph	10*LT kmph		
									1/	4PR		2.7	57	730 3	490	2760	2660	2490	2490	3060		
400/60-15.5 Steel Belted		13.00DC				380			145A8 153A2			3	61	00 3	710	2940	2840	2650	2650	3260		
												3.2	63	330	850	3050	2940	2750	2750	3380		
												3.5	66	670 4	060	3220	3100	2900	2900	3570		
			40.4				0.5					3.6	68	310 4	140	3290	3170	2960	2960	3640		
			404	3	364		2509		148A8			3.8	70	040 4	280	3400	3270	3060	3060	3760		
									155A2			4	72	250 4	410	3500	3370	3150	3150	3870		
									20	PR		4	71	80 4	370	3460	3340	3120	3120	3840		
									152A8 159A2			5 817		170 4	970	3940	3800	3550	3550	4370		
						Rolling	Load Index	Inflation	Recommended Load													
			Unlo Dime		Loaded				Speed													
Size	Rim				Static radius mm	Circumference mm	PR Symbols	Pressure bar	Drive Wheel								Free Rolling					
			SW mm	OD mm					Static kmph	10 kmph	25 kmph	30 kmph	40 kmph	50 kmph	Static kmph			30 h kmpl		50 kmph		
				874	380	2600	20	0.8	1720	1020	870	820	730	660	1700	1440	123	0 1150	1030	930		
		3.00DCX15						1.6	2630	1570	1330	1250	1120	1010	2640	2240	190	0 1790	1600	1440		
400/60-	AG13.00X15.5 1		5.5 404				152A8(148B) 140A8(136B)	2.4	3530	2100	1790	1680	1500	1350	3500	2970	252	0 2370	2120	1910		
15.5	AG10.00X10.0 1							3.2	4350	2590	2200	2070	1850	1670	4250	3610	306	0 2880	2575	2320		
								4	5260	3140	2670	2510	2240	2020	5200	4410	375	0 3530	3150	2840		
								6	5880	3500	2980	2800	2500	2240	5860	4970	422	0 3980	3550	3150		

Note: For above mentioned size 140 A8 is no longer active for production. Steel Belt available in 16, 20 PR only.

