

HRR 200 - Technical Specifications

Agriculture | Radial | R-1 | TL | 7 Years



Salient Features & Benefits

HRR 200 High-performance radial tyre for harvesters. Designed for superior field grip, stubble resistance, and soil care.

High Traction & Self-Cleaning

- Optimized lug design with unique dual mud breaker.
- Delivers excellent grip in wet or tilled fields and sheds mud for uninterrupted operations

Low Soil Compaction

- Wider footprint with uniform pressure distribution
- Protects soil structure during harvesting, improving productivity and reducing rutting in operation.

Stubble & Puncture Resistance

- Special Stubble-Resistant (SSR) compound
- Defends against sharp stubble damage and improves overall tyre durability

Operational Stability

- Reinforced construction with steel-belted casing.
- Maintains stability and control even on uneven, soft, or hilly terrain & protect against punctures

Machineries



Harvester

Standard: ProductComponent.International Standards

Dimensions ProductComponent.International Standards

ECE	E11*106R00/20*10354*00
Tyre Size	620/75R30 CHO (SB)
Rec Rim	DW20B
Alternate Rim	-
PR & LI/SI	169 A8 / B
Section Width (mm)	625
Overall Diameter (mm)	1692
Static Load Radius (mm)	765
Rolling Circumference (mm)	5060
Type	TL

Note: Section Width And Overall Diameter Are Unloaded Dimensions.

CHO

km/h / bar	1.2	1.6	2	2.4	2.8	3.2
10	6120	7470	8210	8730	9580	10440
15	5610	6850	7520	8000	8780	9570

Harvester Application

km/h / bar	1.2	1.6	2	2.4	2.8	3.2
10	5100	6230	6840	7280	7980	8700
15	4560	5560	6110	6500	7130	7770
25	3770	4610	5060	5380	5910	6440
30	3640	4440	4880	5190	5690	6210
40	3400	4150	4560	4850	5320	5800
50	3400	4150	4560	4850	5320	5800
65	6120	7470	8210	8730	9580	10440

The product information presented in this publication is provided for general reference and may be updated or revised without prior notification. Mahansaria Tyres Pvt. Ltd. or its subsidiaries make no guarantees regarding the absence of errors, omissions, or inaccuracies in the material.

All content featured in this publication or on our website is the sole property of Mahansaria Tyres Pvt. Ltd. and is protected under applicable intellectual property and industrial laws. No part of this material may be copied, reproduced, stored, shared, or distributed in any format: digital, print, or otherwise, without obtaining prior written authorisation from Mahansaria Tyres Pvt. Ltd.

Note: All tyres confirm to ETRTO standards.