



LOAD CERTIFICATE : 620/75R26 Steel Belted

Brand: ASCENSO

Tread Pattern : HRR 200

LSI : 167 A8

Tyre Construction: Radial

Type: Tubeless

Main Applications: Harvester

TRA Code : R-1



Salient Features

- Pattern optimised for **quiet running**
- Optimized carcass for **better operational stability, roadability and manoeuvring**
- Specially designed compound suitable for **high load carrying capacity**



Technical Specification

Size	Rim	Unloaded dimension		Loaded Static	Rolling Circumference	Load Index	Infl.	Recommended load, kg (lbs)						
		SW	OD	Radius			press.	Speed, km/h (mph)					High Torque	Cyclic Application
		mm	mm	mm	mm	Speed	bar	10	15	25	30	40	10	10
		in	in	in	in	Symbol	psi	6	9	16	19	25	6	6
620/75R26 Steel Belted	DW20B	625 24.6	1590 62.5	714 28.1	4755 187.2	167 A8	1.6	5850	5230	4630	4170	3900	4170	---
							23	12890	11520	10200	9190	8590	9190	
							2.0	6420	5740	5080	4580	4280	4580	
							29	14140	12640	11190	10090	9430	10090	
							2.4	6840	6110	5420	4880	4560	4880	
							35	15070	13460	11940	10750	10040	10750	
							2.8	7490	6690	5930	5340	4990	5340	
							41	16500	14740	13060	11760	10990	11760	
							3.2	8180	7300	6470	5830	5450	5830	
							46	18020	16080	14250	12840	12000	12840	
							4	---	---	---	---	---	---	
58	---	---	---	---	---	---	20420							

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover