



LOAD CERTIFICATE: 700/40 – 22.5

Brand: ASCENSO

Tread Pattern : FTB 190

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Baler and Trailers

TRA Code : I-3



Salient Features

Optimized Flotation Design:

- Reduces soil compaction
- Generates traction
- Better self cleaning properties

Enhanced Carcass Construction:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
							Free rolling				Drive wheel				
		mm	mm				Bar	10	25	40	50	10	25	40	50
In	in	Psi	6	16	25	31	6	16	25	31					
700/40-22.5	24	727 28.6	1140 44.9	521 20.5	3410 134.3	16PR 166 A8 FR 162 B FR 154A8 DW 150 B DW	2	6370	5410	4550	4100	4510	3830	3220	2898
							29	14014	11902	10010	9020	9922	8426	7084	6376
							2.2	6730	5720	4810	4330	4760	4050	3400	3060
							32	14806	12584	10582	9526	10472	8910	7480	6732
							2.4	7080	6020	5060	4550	5010	4260	3580	3222
							35	15576	13244	11132	10010	11022	9372	7876	7088
							2.6	7420	6310	5300	4770	5250	4460	3750	3375
							38	16324	13882	11660	10494	11550	9812	8250	7425

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com