



FTB 190 : 800/45 – 26.5

Brand: ASCENSO

Tread Pattern : FTB 190

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Baler and Trailers

TRA Code : I-3



Salient Features

Optimized Flotation Design:

- Reduces soil compaction
- Generates traction
- Better self cleaning properties

Enhanced Carcass Construction:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Recommended load , kg (lbs)								
		SW	OD				Speed , km/h (mph)								
							Free rolling				Drive wheel				
							Bar	10	25	40	50	10	25	40	50
Mm	mm	mm	mm	Psi	6	16	25	31	6	16	25	31			
In	in	in	In												
800/45-26.5	24	828 32.5	1393 54.8	634 24.9	4167 164	16PR 177 A8 FR 173 B FR 164 A8 DW 160 B DW	1.7	8790	7470	6280	5650	6020	5120	4300	3870
							25	19338	16434	13816	12430	13244	11264	9460	8514
							1.8	9090	7720	6490	5840	6230	5300	4450	4005
							26	19998	16984	14278	12848	13706	11660	9790	8811
							2	9660	8210	6900	6210	6620	5630	4730	4257
							29	21252	18062	15180	13662	14564	12386	10406	9365
							2.2	10220	8690	7300	6570	7000	5950	5000	4500
							32	22484	19118	16060	14454	15400	13090	11000	9900

Note: All tyres confirm to ETRTO standards

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover