



# LOAD CERTIFICATE: 10.0/75-15.3 (260/70-15.3)

**Brand:** ASCENSO

**Tread Pattern :** IMB 160

**Ply Rating :** 10

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Implements.

Balers and Trailer

**TRA Code :** I-2



New Product Release

**Optimum Implement Design:**

Minimises soil compaction and protects the grass land

**Strong Nylon Carcass:**

Ensures high load carrying capacity



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg ( lbs)										
		SW	OD				Speed , km/h ( mph)										
		mm	mm				Free rolling				Drive wheel						
		in	in				mm	mm	Bar	10	25	40	50	10	25	40	50
							in	in	Li/SI	Psi	6	16	25	31	6	16	25
10.0/75-15.3 (260/70-15.3)	9	264 10.6	760 29.9	348 13.7	2274 89.5	10 PR 123 A8 FR 111 A8 FW	3	1860	1580	1330	1200	1320	1120	940	846		
							44	4092	3476	2926	2640	2904	2464	2068	1861		
							3.3	1970	1680	1410	1270	1390	1180	990	891		
							48	4334	3696	3102	2794	3058	2596	2178	1960		
							3.6	2070	1760	1480	1330	1460	1240	1040	936		
							52	4554	3872	3256	2926	3212	2728	2288	2059		
							<b>3.9</b>	<b>2170</b>	<b>1840</b>	<b>1550</b>	<b>1400</b>	<b>1530</b>	<b>1300</b>	<b>1090</b>	<b>981</b>		
						<b>57</b>	<b>4774</b>	<b>4048</b>	<b>3410</b>	<b>3080</b>	<b>3366</b>	<b>2860</b>	<b>2398</b>	<b>2158</b>			
						14 PR 130 A8 FR 118 DW	4.1	2240	1900	1600	1440	1570	1330	1120	1108		
							59	4928	4180	3520	3168	3454	2926	2464	2218		
							4.5	2370	2010	1690	1520	1650	1400	1180	1062		
							65	5214	4422	3718	3344	3630	3080	2596	2336		
							5	2520	2140	1800	1620	1750	1490	1250	1125		
							73	5544	4708	3960	3564	3850	3278	2750	2475		
<b>5.5</b>	<b>2660</b>	<b>2260</b>	<b>1900</b>	<b>1710</b>	<b>1850</b>		<b>1570</b>	<b>1320</b>	<b>1188</b>								
<b>80</b>	<b>5852</b>	<b>4972</b>	<b>4180</b>	<b>3762</b>	<b>4070</b>	<b>3454</b>	<b>2904</b>	<b>2614</b>									

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification