



LOAD CERTIFICATE: 11.5/80-15.3

Brand: ASCENSO

Tread Pattern : IMB 160

Ply Rating : 16

Tyre Construction: Bias

Type: Tube Less

Main Applications: Implements.

Balers and Trailer

TRA Code : I-2



New Product Release

Optimum Implement Design:

Minimises soil compaction and protects the grass land

Strong Nylon Carcass:

Ensures high load carrying capacity



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg (lbs)								
							Speed , km/h (mph)								
		SW	OD				Free rolling				Drive wheel				
		mm	mm	mm	mm	LI/SI	Bar	10	25	40	50	10	25	40	50
		In	in	in	in		Psi	6	16	25	31	6	16	25	31
11.5/80-15.3	9	290 11.4	845 33.2	383 15.0	2528 99.5	14 PR 139 A8 FR 126 A8 DW	3.6	2880	2450	2060	1850	2020	1710	1440	1296
							52	6336	5390	4532	4070	4444	3762	3168	2851
							3.9	3020	2570	2160	1940	2110	1800	1510	1359
							57	6644	5654	4752	4268	4642	3960	3322	2990
							4.3	3210	2730	2290	2060	2240	1900	1600	1440
							62	7062	6006	5038	4532	4928	4180	3520	3168
							4.75	3400	2890	2430	2190	2380	2020	1700	1530
							69	7480	6358	5346	4818	5236	4444	3740	3366
		16 PR 141 A8 FR 128 A8 DW	4.1	3070	2610	2190	1970	2140	1820	1530	1377				
			59	6754	5742	4818	4334	4708	4004	3366	3029				
			4.5	3230	2750	2310	2080	2270	1930	1620	1458				
			65	7106	6050	5082	4576	4994	4246	3564	3208				
			4.9	3400	2890	2430	2190	2380	2020	1700	1530				
			71	7580	6358	5346	4818	5236	4444	3740	3366				
			5.4	3610	3060	2575	2320	2520	2140	1800	1620				
			78	7942	6732	5665	5104	5544	4708	3960	3664				

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification