



# LOAD CERTIFICATE: 13.0/65-18

**Brand:** ASCENSO

**Tread Pattern :** IMB 160

**Ply Rating :** 16

**Tyre Construction:** Bias

**Type:** Tube Less

**Main Applications:** Implements.

Balers and Trailer

**TRA Code :** I-2



## New Product Release

### **Optimum Implement Design:**

Minimises soil compaction and protects the grass land

### **Strong Nylon Carcass:**

Ensures high load carrying capacity



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Free/ Drive Wheel	Recommended load , kg ( lbs)								
		SW	OD				Speed , km/h ( mph)								
		mm	mm	mm	mm	Free rolling				Drive wheel					
		In	in	in	in	LI/SI	Bar	10	25	40	50	10	25	40	50
						Psi	6	16	25	31	6	16	25	31	
13.0/65-18	11	336 13.2	890 35.0	408 16.0	2662 104.8	16 PR 144 A8 FR 131 A8 DW	3.7	3220	2820	2370	2130	2320	1980	1660	1494
							54	7304	6204	5214	4686	5104	4356	3652	3287
							4.1	3530	3000	2520	2270	2460	2090	1760	1584
							59	7766	6600	5544	4994	5412	4598	3872	3485
							4.5	3720	3170	2660	2390	2600	2210	1860	1674
							65	8184	6974	5852	5258	5720	4862	4092	3683
							<b>4.9</b>	<b>3920</b>	<b>3330</b>	<b>2800</b>	<b>2520</b>	<b>2730</b>	<b>2320</b>	<b>1950</b>	<b>1755</b>
							<b>71</b>	<b>8624</b>	<b>7326</b>	<b>6160</b>	<b>5544</b>	<b>6006</b>	<b>5104</b>	<b>4290</b>	<b>3861</b>

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification