



LOAD CERTIFICATE: 16.9-24

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)												
		Speed , km/h(mph)																		
		SW	OD					Field Operation			Road Operation; Not High and Sustained Torque									
								High Torque	Low Torque											
								mm	mm	mm	mm	Bar	10	10	20	Static	10	20	30	40
								in	in	in	in	Psi	6	6	12		6	16	20	25
16.9-24	W15L	429 16.9	1333 52.5	604 23.8	3987 157.0	8PR	1.5	2090	2930	2400	4490	2930	2400	2090	1950					
							22	4600	6450	5290	9890	6450	5290	4600	4300					
							133 A8	1.65	2200	3090	2530	4740	3090	2530	2200	2060				
								24	4850	6810	5570	10440	6810	5570	4850	4540				
						12PR	2.2	2770	3890	3190	5960	3890	3190	2770	2590					
							32	6100	8570	7030	13130	8570	7030	6100	5700					
							143A8	2.4	2920	4090	3350	6270	4090	3350	2920	2725				
								35	6430	9010	7380	13810	9010	7380	6430	6000				

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification