



LOAD CERTIFICATE : 16.9-26

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 10

Main Applications:2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		Speed , km/h(mph)													
		Field Operation						Road Operation; Not High and Sustained Torque							
		High Torque	Low Torque												
		Bar	10					10	20	Static	10	20	30	40	
Psi	6	6	12	6	16	20	25								
16.9-26	W15L	429 16.80	1384 54.40	629 24.70	4140 162.90	10PR 133 A8	1.6	1990	2790	2290	4280	2790	2290	1990	1860
							23	4380	6150	5040	9430	6150	5040	4380	4100
							1.7	2070	2900	2370	4440	2900	2370	2070	1930
							25	4560	6390	5220	9780	6390	5220	4560	4250
							1.8	2140	3000	2460	4600	3000	2460	2140	2000
							26	4710	6610	5420	10130	6610	5420	4710	4410
							1.9	2200	3090	2530	4740	3090	2530	2200	2060
							28	4850	6810	5570	10440	6810	5570	4850	4540

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com