



LOAD CERTIFICATE: 16.9-34

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
								Speed , km/h(mph)							
		SW	OD					Field Operation			Road Operation; Not High and Sustained Torque				
								High Torque	Low Torque						
								mm	mm	mm	mm	Bar	10	10	20
		in	in	in	in		Psi	6	6	12	6	16	20	25	
16.9-34	W15L	429 16.9	1587 62.5	731 28.8	4747 186.9	8PR 139 A8	1.5	2460	3450	2830	5290	3450	2830	2460	2300
							22	5420	7600	6230	11650	7600	6230	5420	5070
							1.65	2600	3650	2990	5590	3650	2990	2600	2430
							24	5730	8040	6590	12310	8040	6590	5730	5350

Note: All tyres confirm to ETRTO standards
Figures in bold are the recommended specification