



LOAD CERTIFICATE : 8.00-16

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 6

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		Speed , km/h(mph)													
		Field Operation						Road Operation; Not High and Sustained Torque							
		High Torque	Low Torque												
		Bar	10					10	20	Static	10	20	30	40	
Psi	6	6	12	6	16	20	25								
8.00-16	6LB	211 8.3	790 31.1	362 14.2	2363 93.03	6 PR 88 A8	1.6	540	750	620	1150	750	620	540	500
							23	1190	1650	1370	2530	1650	1370	1190	1100
							1.7	560	780	640	1200	780	640	560	520
							25	1230	1720	1410	2640	1720	1410	1230	1150
							1.8	580	810	660	1240	810	660	580	540
							26	1280	1780	1450	2730	1780	1450	1280	1190
							1.9	600	840	690	1290	840	690	600	560
							28	1320	1850	1520	2840	1850	1520	1320	1230

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com