



LOAD CERTIFICATE: 8.3-32

Brand: ASCENSO

Tread Pattern : TDB 120

Ply Rating : 8

Main Applications: 2WD Tractor

TRA Code : R-1



Salient Features

Wider Lugs:

Easy to penetrate the soil ,generates optimum traction and ensures comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tyre against failures



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommended load , kg(lbs)							
		Speed , km/h(mph)													
		Field Operation						Road Operation; Not High and Sustained Torque							
		High Torque	Low Torque												
		Bar	10					10	20	Static	10	20	30	40	
		Psi	6					6	12		6	16	20	25	
8.3-32	W7	211 8.3	1195 47.0	565 22.0	3574 140.7	8PR 111 A6 107 A8	2.5	1020	1330	1140	2190	1330	1140	950	855
							36	2250	2930	2510	4820	2930	2510	2090	1880
							2.7	1060	1390	1190	2280	1390	1190	990	891
							39	2330	3060	2620	5020	3060	2620	2180	1960
							2.9	1100	1440	1240	2370	1440	1240	1030	927
							42	2420	3170	2730	5220	3170	2730	2270	2040
							3.2	1170	1530	1310	2510	1530	1310	1090	975
							46	2580	3370	2890	5530	3370	2890	2400	2150

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification