



# LOAD CERTIFICATE: 540/65R28

**Brand:** ASCENSO

**Tread Pattern :** TDR 650

**Tyre Construction:** Radial

**LSI :** 149 D

**Type:** Tube Less

**Main Applications:** 4WD Tractor

**TRA Code :** R-1W



## Salient Features

### **Optimum Tread Design:**

Maximum performance in field and on road operations

### **First in the Industry with Dual Mud Breakers:**

Ensure better self-cleaning

### **Greater Lug Overlap:**

Provides safe and comfortable ride at high speeds



# Technical Specification

Size	W	Rim	Unloaded Dimension		SLR	RC	Load Index	PR Symbols	Recommended load, kg (lbs)								
			SW	OD					mm	mm	Speed, km/h (mph)						
											Mixed application						
											Bar	Static	10	25	30	40	50
mm	mm	mm	mm	Psi	6	16	19	25	31	40							
in	in	in	in														
540/65 R 28	W16L	530 20.8	1413 55.6	646 25.4	4226 166.4	149 D	1.2	4490	2930	2310	2240	2140	2050	1950			
							17	9890	6450	5090	4930	4710	4520	4300			
							1	4990	3260	2570	2500	2380	2280	2170			
							20	10990	7180	5660	5510	5240	5020	4780			
							1.7	5750	3750	2960	2880	2740	2630	2500			
							25	12670	8260	6520	6340	6040	5790	5510			
							2.1	6740	4400	3470	3370	3210	3080	2930			
							30	14850	9690	7640	7420	7070	6780	6450			
							2.4	7480	4880	3850	3740	3560	3410	3250			
							35	16480	10750	8480	8240	7840	7510	7160			

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6<sup>th</sup> Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: [www.ascensotyres.com](http://www.ascensotyres.com)