



LOAD CERTIFICATE: 600/65R34

Brand: ASCENSO

Tread Pattern : TDR 650

Tyre Construction: Radial

LSI : 157 D

Type: Tube Less

Main Applications: 4WD Tractor

TRA Code : R-1W



Salient Features

Optimum Tread Design:

Maximum performance in field and on road operations

First in the Industry with Dual Mud Breakers:

Ensure better self-cleaning

Greater Lug Overlap:

Provides safe and comfortable ride at high speeds



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
		SW	OD					Speed, km/h (mph)						
								Mixed application						
								Bar	10	25	30	40	50	65
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	
in	in	in	in	in	in	in	Psi	Static	6	16	19	25	31	40
600/65 R 34	DW20B	611 24.0	1644 64.7	754 29.6	4917 193.5	157 D	1.2	5700	3720	2940	2850	2720	2600	2480
							17	12560	8190	6480	6280	5990	5730	5460
							1	6330	4130	3260	3160	3010	2890	2750
							20	13940	9100	7180	6960	6630	6370	6060
							1.7	7270	4740	3740	3630	3460	3320	3160
							25	16010	10440	8240	8000	7620	7310	6960
							2.1	8530	5570	4400	4270	4060	3900	3710
							30	18790	12270	9690	9410	8940	8590	8170
							2.4	9490	6190	4890	4740	4520	4330	4125
35	20900	13630	10770	10440	9960	9540	9090							

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Pvt. Ltd.

612, 6th Floor, Maker Chambers IV, Nariman Point, Mumbai 400021, Maharashtra, India

T: +91 22 4348 1600 Website: www.ascensotyres.com