



LOAD CERTIFICATE: 280/85R28

Brand: ASCENSO

Tread Pattern : TDR 850

Tyre Construction: Radial

LSI : 118D

Type: Tube Less

Main Applications: 2WD & 4WD Tractor

TRA Code : R-1W



Salient Features

Tractor tyres designed with a unique mud breaker:

- Low soil compaction
- High traction
- Excellent driving experience



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
		Speed, km/h (mph)												
		SW	OD	Mixed application										
		mm	mm	mm	mm		Bar	Static	10	25	30	40	50	65
		in	in	in	in		Psi		6	16	19	25	31	40
280/85 R28	W10	292 11.5	1187 46.7	552 21.7	3551 139.8	118 D	0.8	1930	1260	1000	970	920	880	840
							12	4250	2780	2200	2140	2030	1940	1850
							1.0	2210	1440	1140	1100	1050	1010	960
							15	4870	3170	2510	2420	2310	2220	2110
							1.2	2480	1620	1280	1240	1180	1130	1080
							17	5460	3570	2820	2730	2600	2490	2380
							1.4	2760	1800	1420	1380	1310	1260	1200
							20	6080	3960	3130	3040	2890	2780	2640
							1.6	3040	1980	1560	1520	1450	1390	1320
23	6700	4360	3440	3350	3190	3060	2910							

Note: All tyres confirm to ETRTO standards
Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover