



LOAD CERTIFICATE: 420/85R28

Brand: ASCENSO

Tread Pattern : TDR 850

Tyre Construction: Radial

LSI : 139D

Type: Tube Less

Main Applications: 2WD & 4WD Tractor

TRA Code : R-1W



Salient Features

Tractor tyres designed with a unique mud breaker:

- Low soil compaction
- High traction
- Excellent driving experience



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	Load Index PR Symbols	Inflation Pressure	Recommended load, kg (lbs)						
								Speed, km/h (mph)						
								Mixed application						
		SW	OD	Bar	Static			10	25	30	40	50	65	
		mm	mm				mm	mm	Psi	6	16	19	25	31
in	in	in	in											
420/85 R28	W15L	438 17.2	1425 56.1	651 25.6	4262 167.8	139 D	0.8	3570	2330	1840	1780	1700	1630	1550
							12	7860	5130	4050	3920	3740	3590	3410
							1	4070	2660	2100	2040	1940	1860	1770
							15	8960	5860	4630	4490	4270	4100	3900
							1.2	4580	2990	2360	2290	2180	2090	1990
							17	10090	6590	5200	5040	4800	4600	4380
							1.4	5080	3320	2620	2540	2420	2320	2210
							20	11190	7310	5770	5590	5330	5110	4870
							1.6	5590	3650	2880	2790	2660	2550	2430
							23	12310	8040	6340	6150	5860	5620	5350

Note: All tyres confirm to ETRTO standards
Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover