



TSB 110: 10.00-16

Brand: ASCENSO

Tread Pattern : TSB 110

Ply Rating : 10

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code: F2



Salient Features

Wider Centre Rib:

Ease in steering & prevents damage to the grass land

High Strength Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)									
		SW	OD					Speed, km/h(mph)									
		mm	mm	mm	mm			Mixed Application									
		in	in	in	In		Bar	Static	10	20	25	30	40				
				Psi	6	12	15		20	25							
10.00-16	W8L	274	894	405	2674	10PR	2.6	3090	2060	1420	1320	1140	1030				
							38	6810	4540	3130	2910	2510	2270				
							2.8	3240	2160	1490	1380	1200	1080				
							41	7140	4760	3280	3040	2640	2380				
							10.8	35.2	15.9	105.3	3.1	3450	2300	1590	1470	1280	1150
							45	7600	5070	3500	3240	2820	2530				
							3.4	3650	2430	1680	1560	1350	1215				
							49	8040	5350	3700	3440	2970	2680				

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification