



LOAD CERTIFICATE: 6.00-16

Brand: ASCENSO

Tread Pattern : TSB 110

Ply Rating : 6

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code: F2



Salient Features

Wider Centre Rib:

Ease in steering & prevents damage to the grass land

High Strength Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
		mm	mm					Mixed Application					
		in	in					mm	mm	in	in	Bar	Psi
6.00-16	4.50E	159	739	341	2211	6PR	2.7	1290	860	590	550	480	430
							39	2840	1890	1300	1210	1060	950
							3.0	1380	920	630	590	510	460
							44	3040	2030	1390	1300	1120	1010
		6.3	29.1	13.4	87.0	85 A8	3.3	1470	980	680	630	540	490
							48	3240	2160	1500	1390	1190	1080
							3.6	1550	1030	710	660	570	515
							52	3410	2270	1560	1450	1260	1130

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification