



LOAD CERTIFICATE: 7.50-16

Brand: ASCENSO

Tread Pattern : TSB 110

Ply Rating : 8

Tyre Construction: Bias

Type: Tube Type

Main Applications: 2 WD Tractor

TRA Code: F2



Salient Features

Wider Centre Rib:

Ease in steering & prevents damage to the grass land

High Strength Nylon Carcass:

Provides stability to the machine & ensures durability

Special Tread Compound:

Provides longer tyre life
Resistance to puncture



Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)										
		SW	OD					Speed, km/h(mph)										
		mm	mm	mm	mm			Mixed Application										
		in	in	in	in		Bar	Static	10	20	25	30	40					
							Psi		6	12	15	20	25					
7.50-16	5.50F	203	808	369	2417	8PR	2.9	1950	1300	900	830	720	650					
							42	4300	2860	1980	1830	1590	1430					
							3.2	2070	1380	950	880	770	690					
							46	4560	3040	2090	1940	1700	1520					
							8.0	31.8	14.5	95.2	99 A8	3.5	2190	1460	1010	930	810	730
							51	4820	3220	2220	2050	1780	1610					
							3.85	2330	1550	1070	990	860	775					
							56	5130	3410	2360	2180	1890	1710					

Note: All tyres confirm to ETRTO standards

Figures in bold are the recommended specification