



## LOAD CERTIFICATE : 9.00-16

**Brand:** ASCENSO

**Tread Pattern :** TSB 110

**Ply Rating :** 10

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** 2 WD Tractor

**TRA Code:** F2



## Salient Features

### **Wider Centre Rib:**

Ease in steering & prevents damage to the grass land

### **High Strength Nylon Carcass:**

Provides stability to the machine & ensures durability

### **Special Tread Compound:**

Provides longer tyre life  
Resistance to puncture



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
								Mixed Application					
		mm	mm					10	20	25	30	40	
		in	in										Bar
						Psi							
9.00-16	6.0F	234	856	389	2561	10PR	3.2	2820	1880	1300	1200	1040	940
							46	6210	4140	2860	2640	2290	2070
							3.5	2970	1980	1370	1270	1100	990
							51	6540	4360	3020	2800	2420	2180
		9.2	33.7	15.3	100.8	111 A8	3.8	3120	2080	1440	1330	1150	1040
							55	6870	4580	3170	2930	2530	2290
							<b>4.15</b>	3270	2180	1500	1400	1210	<b>1090</b>
							60	7200	4800	3300	3080	2670	2400

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification