



## LOAD CERTIFICATE: 6.00-16

**Brand:** ASCENSO

**Tread Pattern :** TSB 111

**Ply Rating:** 8

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:** 2 WD Tractor

**TRA Code :** F-2



## Salient Features

### **Unique Dumbbell Pattern:**

Reduces block tearing & shoulder block deformation

### **Strong Nylon Carcass:**

Provides stability to the machine & ensures durability

### **Special Tread Compound:**

Provides longer tyre life  
Resistance to puncture



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
		mm	mm	Mixed Application									
		in	in	mm	mm		Bar	Static	10	20	25	30	40
mm	mm	in	in	Psi	6	12	15		20	25			
6.00-16	4.50E	165 6.5	739 29.0	341 13.4	2211 87.0	8 PR 91 A8	3.4	1560	1040	720	670	580	520
							49	3440	2290	1590	1480	1280	1150
							3.7	1650	1100	760	700	610	550
							54	3630	2420	1670	1540	1340	1210
							4.1	1740	1160	800	740	640	580
							59	3830	2560	1760	1630	1410	1280
							<b>4.5</b>	<b>1850</b>	<b>1230</b>	<b>850</b>	<b>790</b>	<b>680</b>	<b>615</b>
							<b>65</b>	<b>4070</b>	<b>2710</b>	<b>1870</b>	<b>1740</b>	<b>1500</b>	<b>1350</b>

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification