



## LOAD CERTIFICATE:7.50-16

**Brand:** ASCENSO

**Tread Pattern :** TSB 111

**Ply Rating:** 8

**Tyre Construction:** Bias

**Type:** Tube Type

**Main Applications:**2 WD Tractor

**TRA Code :** F-2



## Salient Features

### **Unique Dumbbell Pattern:**

Reduces block tearing & shoulder block deformation

### **Strong Nylon Carcass:**

Provides stability to the machine & ensures durability

### **Special Tread Compound:**

Provides longer tyre life  
Resistance to puncture



# Technical Specification

Size	Rim	Unloaded Dimension		SLR	RC	LI/SI or PR	Inflation Pressure	Recommend load, kg (lbs)					
		SW	OD					Speed, km/h(mph)					
								Mixed Application					
								Bar	Static	10	20	25	30
Psi	6	12	15	20	25								
7.50-16	5.50F	203 8.0	808 31.8	369 14.5	2417 95.1	8 PR 99 A8	2.9	1950	1300	900	830	720	650
							42	4300	2860	1980	1830	1590	1430
							3.2	2070	1380	950	880	770	690
							46	4560	3040	2090	1940	1700	1520
							3.5	2190	1460	1010	930	810	730
							51	4820	3220	2220	2050	1780	1610
							<b>3.85</b>	<b>2330</b>	<b>1550</b>	<b>1070</b>	<b>990</b>	<b>860</b>	<b>775</b>
							<b>56</b>	<b>5130</b>	<b>3410</b>	<b>2360</b>	<b>2180</b>	<b>1890</b>	<b>1710</b>

**Note:** All tyres confirm to ETRTO standards

Figures in bold are the recommended specification