



LOAD CERTIFICATES: 600/50R22.5 (SB)

Brand: ASCENSO

Tread Pattern : FTR 170

Tyre Construction: Radial

LSI : 159 D

Type: Tube Less

Main Applications: Implements, Trailers, Slurry Tankers and Dump Trailer

TRA Code : IMP



Salient Features

Steel Belted Directional Tread for Superior Traction:

- Homogenous Pattern for On Road and Farm Applications
- Tyres Designed for High load and Speed Operations.
- Ensure traction and self-cleaning during field operation.
- Enhanced Roadability ensuring Better Mileage.



Technical Specification

Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	Load Index / Speed Index	Inflation Pressure	Recommended load, kg (lbs)						
		Speed, km/h (mph)												
		Mixed application												
		bar	10					25	30	40	50	65		
		psi	Static					6	16	19	25	31	40	
mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm
in	in	in	in	in	in	in	in	in	in	in	in	in	in	in
600/50R22.5 (SB)	AG20.00	611 24.1	1172 46.1	534 21.0	3505 138.0	159 D	2.4	6670	5220	4580	4380	3940	3510	2900
							35	14690	11500	10090	9650	8680	7730	6390
							2.8	7570	5920	5200	4970	4470	3980	3290
							41	16670	13040	11450	10950	9850	8770	7250
							3.2	8330	6520	5720	5470	4920	4380	3620
							46	18350	14360	12600	12050	10840	9650	7970
							3.6	9130	7150	6270	5990	5400	4800	3970
							52	20110	15750	13810	13190	11890	10570	8740
							4	10060	7880	6910	6610	5950	5290	4375
							58	22160	17360	15220	14560	13110	11650	9640

Note: All tyres conform to ETRTO standards

Figures in bold are the recommended specification

Ascenso is a new-age off-highway tyre brand that caters to three key global segments: Agriculture, Industrial & Construction and Earthmover

Mahansaria Tyres Private Limited, 3rd Floor, Peninsula Chambers, Peninsula Corporate Park, G K Marg, Lower Parel West, Mumbai Maharashtra - 400013, India.

T: +91 22 4348 1600 Website: www.ascensotyres.com