

# FARMAX R70

**FEATURE**

- Greater lug overlap

**BENEFITS**

- More lugs in footprint
- Better stability

**FEATURE**

- Larger inner volume

**BENEFITS**

- Reduced soil compaction
- Increased load carrying capacity



**FEATURES**

- Reduced space between lugs
- Mud breaker at the centre

**BENEFITS**

- Better roadability
- Increased service life
- Self cleaning

**FEATURE**

- Rounded shoulder

**BENEFIT**

- Less soil disturbance

**FEATURE**

- Dual lug angle

**BENEFITS**

- Superior traction
- Better Roadability


**FEATURE**

- Wider tread

**BENEFITS**

- Reduced soil compaction
- Increased footprint

## MACHINERY



Tractor

| Size      | LI/SS      | Rim                | Unloaded dimension |       | SLR  | RC    | Infl. Press | Speed, km/h (mph) |       |                        |       |       |       |       |
|-----------|------------|--------------------|--------------------|-------|------|-------|-------------|-------------------|-------|------------------------|-------|-------|-------|-------|
|           |            |                    | SW                 | OD    |      |       |             | Static            | 10    | 25                     | 40    | 50    | 65    | 70    |
|           |            |                    | mm/in              | mm/in |      |       |             |                   | 6     | 15                     | 25    | 31    | 40    | 43    |
| 710/70R42 | 173D/176A8 | DW 23 B<br>DW 25 B | 715                | 2061  | 932  | 6119  | 1.8         | 12630             | 8240  | 6510                   | 6010  | 5760  | 5490  | 5000  |
|           |            |                    | 28.1               | 81.1  | 36.7 | 240.9 | 26          | 27820             | 18150 | 14340                  | 13240 | 12690 | 12090 | 11010 |
|           |            |                    |                    |       |      |       | 2           | 13430             | 8760  | 6920                   | 6390  | 6130  | 5840  | 5310  |
|           |            |                    |                    |       |      |       | 29          | 29580             | 19300 | 15240                  | 14070 | 13500 | 12860 | 11700 |
|           |            |                    |                    |       |      |       | 2.2         | 14210             | 9270  | 7320                   | 6770  | 6490  | 6180  | 5620  |
|           |            |                    |                    |       |      |       | 32          | 31300             | 20420 | 16120                  | 14910 | 14300 | 13610 | 12380 |
|           |            |                    |                    |       |      |       | 2.4         | 14950             | 9750  | 7700                   | 7120  | 6830  | 6500  | 5920  |
|           |            |                    |                    |       |      |       | 35          | 32930             | 21480 | 16960                  | 15680 | 14320 | 16520 | 13040 |
|           |            |                    |                    |       |      |       |             |                   |       | maximum Load, kg (lbs) |       |       |       |       |