

FARMAX R65

FEATURES

- Greater lug overlap
- More lugs in footprint

BENEFITS

- Improved roadability for haulage
- Safe and comfortable ride
- Less vibration on road

FEATURES

- Mud breaker
- Variable groove contour
- Smooth flowing step groove

BENEFITS

- Better self cleaning properties
- Less soil from field to road



FEATURE

- R1-W tread depth

BENEFIT

- Long service life

FEATURES

- Lower lug angle at shoulder
- Higher lug angle at centre

BENEFITS

- Better traction
- Better ride

FEATURE

- Rounded shoulder

BENEFIT

- Reduced soil disturbance


FEATURE

- Wider tread

BENEFITS

- Lower soil compaction
- Increased footprint area

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed kmph / mph							
				SW	OD				Non cyclic operation				Cyclic operation			
				mm	mm				25	40	50	65	bar	10	15	
				in	in				16	25	31	40	psi	6	9	
480/65R28	142D	TL	W15L W14L	480 18.9	1335 52.6	608 23.9	3962 156	1.8	2580	2650	2450	2350	2240	2.25	3810	3470
								26	5680	5840	5400	5180	4930	33	8390	7640
								2	2740	2820	2610	2500	2380	2.5	4050	3690
								29	6040	6210	5750	5510	5240	36	8920	8130
								2.2	2900	2990	2760	2650	2520	2.75	4280	3910
								32	6390	6590	6080	5840	5550	40	9430	8610
								2.4	3050	3140	2900	2780	2650	3	4510	4110
35	6720	6920	6390	6120	5840	44	9930	9050								

All tires confirms ETRTO T&RA & STRO standards