

FARMAX R70

FEATURE

• Greater lug overlap

BENEFITS

- More lugs in footprint
- · Better stability

FEATURE

• Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity

FEATURE

Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

• Rounded shoulder

BENEFIT

• Less soil disturbance


FEATURE

• Dual lug angle

BENEFITS

- Superior traction
- Better Roadability

MACHINERY



Tractor

Size	LI/SS	Туре	RIm	Unloaded Dimension		01.0			Speed kmph /mph					
				sw	OD	SLR	RC	Infl.Press	Static	10	20	30	40	50
										6	12	19	25	31
				mm mm mm bar				commend	ommend load kg /lbs					
				in	in	in	in	psi		Ticconinicia idaa kg / ibs				
420/70R24	130 A8/B	TL	W12 W13 W14L	430 16.9	1248 49.1	563 22.2	3683 145	0.8	2920	1910	1560	1360	1270	1270
								12	6430	4210	3440	3000	2800	2800
								1	3310	2160	1770	1540	1440	1440
								15	7290	4760	3900	3390	3170	3170
								1.3	3860	2520	2070	1800	1680	1680
								19	8500	5550	4560	3960	3700	3700
								1.6	4370	2850	2340	2030	1900	1900
								23	9630	6280	5150	4470	4190	4190

All tires confirms ETRTO T&RA & STRO standards