

FARMAX R85

FEATURE

- Greater lug overlap

BENEFITS

- More lugs in footprint
- Better stability

FEATURE

- Larger inner volume

BENEFITS

- Reduced soil compaction
- Increased load carrying capacity



FEATURES

- Reduced space between lugs
- Mud breaker at the centre

BENEFITS

- Better roadability
- Increased service life
- Self cleaning

FEATURE

- Rounded shoulder

BENEFIT

- Less soil disturbance

FEATURE

- Dual lug angle

BENEFITS

- Superior traction
- Better Roadability


FEATURE

- Wider tread

BENEFITS

- Reduced soil compaction
- Increased footprint

MACHINERY



Tractor

Size	LI/SS	Type	Rim	Unloaded Dimension		SLR	RC	Infl. Press	Speed, km/h (mph)					
				SW	OD				Static	10	20	30	40	50
				mm/in	mm/in					6	12	19	25	31
												Recommend load kg /lbs		
380/85R28	133 A8/B	TL	W12	390	1357	620	4035	0.8	3150	2060	1690	1470	1370	1370
				12	6940			4540	3720	3240	3020	3020		
			W13	15.4	53.4	24.4	158.9	1	3590	2340	1920	1670	1560	1560
				15	7910			5150	4230	3680	3440	3440		
				1.3	4190	2730	2240	1950	1820	1820				
				19	9230	6010	4930	4300	4010	4010				
				1.6	4740	3090	2530	2200	2060	2060				
				23	10440	6810	5570	4850	4540	4540				