



320/85 R 24 122 A8 (119 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	320/85 R 24	Tread Pattern	RD-01
Tyre size alternative	12.4 R 24	Service description LI SS	122 A8 (119 B)
Type	TL	Permitted Rims	W 11 W 9 W 10
Section Width (mm)	340 320 330	Overall Diameter (mm)	1 152
Loaded Static Radius (mm)	510	Rolling Circumference (mm)	3 420
Speed radius index	550	EAN code	8590341099310
Water 75% (l)	115		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	1 100	1 190	1 275	1 360	-	-	-	-	-	50
-	1 095	1 205	1 305	1 400	1 500	-	-	-	-	-	40
1 045	1 175	1 290	1 400	1 500	1 605	-	-	-	-	-	30
1 270	1 425	1 570	1 700	1 825	1 950	2 250	-	-	-	-	10