

## 460/85 R 38 149 A8 (146 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

## TECHNICAL DATA

Tyre size	460/85 R 38	Tread Pattern	RD-01
Tyre size alternative	18.4 R 38	Service description LI SS	149 A8 (146 B)
Туре	TL	Permitted Rims	<b>W 15</b> W 14
Section Width (mm)	463 453	Overall Diameter (mm)	1 735
Loaded Static Radius (mm)	793	Rolling Circumference (mm)	5 230
Speed radius index	825	EAN code	8590341099587
Water 75% (I)	420		

## LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)									Speed (km/h)		
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	
-	-	2370	2575	2760	3 000	-	-	-	-	-	50
-	2370	2605	2830	3 030	3 250	-	-	-	-	-	40
2 255	2 535	2790	3 030	3 245	3 480	-	-	-	-	-	30
2745	3 080	3 390	3 680	3 945	4 225	4 875	-	-	-	-	10