



## 480/65 R 28 136 D (139 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

### TECHNICAL DATA

<b>Tyre size</b>	480/65 R 28	<b>Tread Pattern</b>	RD-03
<b>Service description LI SS</b>	136 D (139 A8)	<b>Type</b>	TL
<b>Permitted Rims</b>	W 15 L W 14 L W 13	<b>Section Width (mm)</b>	478 468 458
<b>Overall Diameter (mm)</b>	1345	<b>Loaded Static Radius (mm)</b>	611
<b>Rolling Circumference (mm)</b>	4034	<b>Speed radius index</b>	650
<b>EAN code</b>	8590341100870	<b>Water 75% (l)</b>	250

### LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	1720	1880	2060	2240	-	-	-	65
-	-	1625	1805	1975	2165	2350	-	-	-	50
-	1495	1695	1885	2060	2260	2430	-	-	-	40
-	1570	1780	1980	2160	2370	2575	-	-	-	30
1635	1910	2165	2410	2630	2885	3135	3680	-	-	10