



520/85 R 38 155 A8 (152 B) RD-01 TL

- All-round standard tyres for a wide range of applications
- Balanced combination of features for various agricultural applications
- Very good grip and traction with much less slip
- Long service life thanks to the wear-resistant tread compound
- Large ground contact patch and lower operating pressure for less soil compaction

TECHNICAL DATA

Tyre size	520/85 R 38	Tread Pattern	RD-01
Tyre size alternative	20.8 R 38	Service description LI SS	155 A8 (152 B)
Type	TL	Permitted Rims	W 16 W 18
Section Width (mm)	536 556	Overall Diameter (mm)	1 828
Loaded Static Radius (mm)	814	Rolling Circumference (mm)	5 442
Speed radius index	875	EAN code	8590341099594
Water 75% (l)	530		

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)											Speed (km/h)
0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	4	4,4	-
-	-	2865	3105	3330	3550	-	-	-	-	-	50
-	2860	3150	3415	3660	3875	-	-	-	-	-	40
2725	3060	3370	3655	3920	4145	-	-	-	-	-	30
3310	3720	4090	4440	4760	5040	5815	-	-	-	-	10