



## 540/65 R 30 150 D (153 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

### TECHNICAL DATA

<b>Tyre size</b>	540/65 R 30	<b>Tread Pattern</b>	RD-03
<b>Service description LI SS</b>	150 D (153 A8)	<b>Type</b>	TL
<b>Permitted Rims</b>	W 16 L W 18 L W 15 L	<b>Section Width (mm)</b>	532 552 522
<b>Overall Diameter (mm)</b>	1 484	<b>Loaded Static Radius (mm)</b>	667
<b>Rolling Circumference (mm)</b>	4 427	<b>Speed radius index</b>	700
<b>EAN code</b>	8590341100917	<b>Water 75% (l)</b>	330

### LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	2 130	2 325	2 545	2 760	3 080	3 350	-	65
-	-	2 010	2 235	2 440	2 675	2 895	3 235	3 520	-	50
-	1 850	2 100	2 330	2 545	2 790	3 020	3 375	3 650	-	40
-	1 940	2 205	2 450	2 675	2 930	3 175	3 545	3 855	-	30
2 020	2 365	2 680	2 980	3 255	3 565	3 865	4 315	4 690	5 500	10