



## 600/65 R 34 151 D (154 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

### TECHNICAL DATA

<b>Tyre size</b>	600/65 R 34	<b>Tread Pattern</b>	RD-03
<b>Service description LI SS</b>	151 D (154 A8)	<b>Type</b>	TL
<b>Permitted Rims</b>	W 18 L DW 18 L W 16 L	<b>Section Width (mm)</b>	587 587 570
<b>Overall Diameter (mm)</b>	1 632	<b>Loaded Static Radius (mm)</b>	725
<b>Rolling Circumference (mm)</b>	4 850	<b>Speed radius index</b>	775
<b>EAN code</b>	8590341100931	<b>Water 75% (l)</b>	465

### LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	0,6	0,8	1	1,2	1,4	1,6	2	2,4	3	-
-	-	-	2 650	2 900	3 180	3 450	-	-	-	65
-	-	2 505	2 785	3 045	3 335	3 625	-	-	-	50
-	2 300	2 615	2 905	3 175	3 480	3 780	-	-	-	40
-	2 420	2 745	3 050	3 330	3 655	3 970	-	-	-	30
2 520	2 945	3 340	3 710	4 055	4 450	4 830	5 665	-	-	10