650/65 R 38 157 D (160 A8) RD-03 TL

- Reduced soil compaction thanks to large ground contact area and optimal pressure distribution
- Up to 40% higher tension force compared to standard tyres
- High load capacity due to the wide design and the large volume of air
- Outstanding grip and tractive force ensure less slip and much lower fuel consumption
- Maximum speed of 65 km/h on roads, high driving comfort and easy handling

TECHNICAL DATA

Tyre size	650/65 R 38	**Tread Pattern**	RD-03
Service description LI SS	157 D (160 A8)	**Type**	TL
Permitted Rims	**W 18 L** DW 20 B	**Section Width (mm)**	626 646
Overall Diameter (mm)	1 829	**Loaded Static Radius (mm)**	809
Rolling Circumference (mm)	5 410	**Speed radius index**	875
EAN code	8590341100962	**Water 75% (l)**	630

LOAD CAPACITY PER TIRE

Tyre load at pressure (BAR)										Speed (km/h)
0,4	**0,6**	**0,8**	**1**	**1,2**	**1,4**	**1,6**	**2**	**2,4**	**3**	-
-	-	-	3 155	3 450	3 790	4 125	-	-	-	65
-	-	2 985	3 315	3 625	3 980	4 330	-	-	-	50
-	2 740	3 110	3 455	3 780	4 150	4 500	-	-	-	40
-	2 880	3 270	3 630	3 970	4 360	4 745	-	-	-	30
3 000	3 505	3 980	4 420	4 830	5 310	5 775	6 775	-	-	10