

**D304****D305****D311****D316****D322****D323**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	(mm)	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D304	27x8.50-15	6	96B	TL	678	213	13.0	45/310	710/1570	50/30	7.00
		8	101B	TL	678	213	13.0	60/415	825/1820	50/30	7.00
	27x10.50-15	6	98B	TL	691	259	13.0	45/310	750/1650	50/30	8.50
		8	103B	TL	691	259	13.0	60/415	875/1930	50/30	8.50
	10-16.5	8	-/A2	TL	773	264	12.7	60/415	1880/4140	10/5	8.25
		10	-/A2	TL	773	264	12.7	75/520	2135/4720	10/5	8.25
	12-16.5	10	-/A2	TL	831	307	16.6	65/450	2540/5600	10/5	9.75
		12	-/A2	TL	831	307	16.6	80/550	2865/6320	10/5	9.75
	14-17.5	14	-/A2	TL	921	349	18.2	80/550	3875/8540	10/5	10.50
	15-19.5	14	-/A2	TL	1019	389	18.2	70/485	4565/10060	10/5	11.75
31x15.50-15	8	116A3	TL	790	398	20.5	45/310	1250/2760	15/10	13.00	
	10	122A3	TL	790	398	20.5	61/420	1485/3270	15/10	13.00	
31.5x13.00-16.5	10	128A3	TL	765	330	19.0	70/480	1780/3925	15/10	9.75	
33x15.50-16.5	12	137A3	TL	838	393	21.0	70/480	2295/5060	15/10	12.00	
D305	10-16.5	6	-/A2	TL	773	264	16.6	45/310	1590/3500	10/5	8.25
		8	-/A2	TL	773	264	16.6	60/410	1880/4140	10/5	8.25
	12-16.5	8	-/A2	TL	831	307	17.0	50/340	2180/4810	10/5	9.75
		10	-/A2	TL	831	307	17.0	65/450	2540/5600	10/5	9.75
D311	10-16.5	8	-/A2	TL	773	264	15.0	60/410	1880/4140	10/5	8.25
		10	-/A2	TL	773	264	15.0	75/520	2135/4700	10/5	8.25
	12-16.5	10	-/A2	TL	831	307	16.0	65/450	2540/5600	10/5	9.75
		12	-/A2	TL	831	307	16.0	80/550	2865/6310	10/5	9.75
D316	29x11.50-15	10	122A8	TL	730	270	17.0	65/450	1500/3300	40/25	10.00
	31x15.50-15	10	121B	TL	792	391	17.0	60/410	1450/3200	50/30	13.00
D322	10-16.5	8	-/A2	TL	773	264	30.0	60/410	1880/4140	10/5	8.25
		10	-/A2	TL	773	264	30.0	75/520	2135/4710	10/5	8.25
	12-16.5	10	-/A2	TL	831	307	34.5	65/450	2540/5600	10/5	9.75
		12	-/A2	TL	831	307	34.5	80/550	2865/6320	10/5	9.75
D323	10-16.5	10	135A2	TL	773	264	35.0	60/415	2180/4806	10/5	8.25
	12-16.5	12	135	TL	831	307	35.0	65/44	2575/5677	10/5	9.75