

**D313(E-3)****D319(E-3)****D320(E-7)**

PATTERN NAME	SIZE	PLY RATING	LI/SS	TYPE	INFLATED DIMENSION		TREAD DEPTH	INFLATION PRESSURE	MAX. LOAD	MAX. SPEED	RIM WIDTH
					OD(mm)	SW(mm)	[mm]	PSI/kPa	KGS/LBS	KPH/MPH	Inch
D313(E-3)	14.00-24	24	165B	TL	1368	375	25.0	83/575	5150/11350	50/30	10.00
		28	168B	TL	1368	375	25.0	94/650	5600/12340	50/30	10.00
		28	168B	TT	1368	375	25.0	94/650	5600/12340	50/30	10.00
	15.5-25	12	149B	TL	1278	394	25.3	36/250	3250/7150	50/30	12.00
		16	154B	TL	1278	394	25.3	47/325	3750/8250	50/30	12.00
	17.5-25	12	153B	TL	1348	445	29.1	33/225	3650/8050	50/30	14.00
		16	158B	TL	1348	445	29.0	44/300	4250/9350	50/30	14.00
		20	164B	TL	1348	445	29.0	58/400	5000/11000	50/30	14.00
	20.5-25	20	170B	TL	1493	521	32.0	47/325	6000/13200	50/30	17.00
		24	174B	TL	1493	521	32.0	58/400	6700/14770	50/30	17.00
	23.5-25	16	125B	TL	1617	597	41.3	33/225	6150/13600	50/30	19.50
		20	177B	TL	1617	597	41.3	44/300	7300/16100	50/30	19.50
		24	180B	TL	1617	597	41.3	51/350	8000/17600	50/30	19.50
	26.5-25	28	188B	TL	1750	673	38.4	51/350	10000/22000	50/30	22.00
	29.5-25	28	193B	TL	1874	749	35.4	47/325	11500/25400	50/30	25.00
D319(E-3)	23.5-25	20	177B	TL	1617	597	36.1	44/300	7300/16100	50/30	19.50
		24	180B	TL	1617	597	36.1	51/350	8000/17600	50/30	19.50
D320(E-3)	20.5-25	20	170B	TL	1493	521	15.8	47/325	6000/13200	50/30	17.00
	23.1-26	12	153A6	TL	1560	590	27.5	25/175	3650/8050	50/30	20.00
		16	159A6	TL	1560	590	27.5	33/230	4375/9650	50/30	20.00