

**D203****D302****D303****D309****D403**

| PATTERN NAME | SIZE | PLY RATING | LOAD INDEX | | TYPE | INFLATED DIMENSION | | TREAD DEPTH (mm) | INFLATION PRESSURE (PSI/kPa) | MAX. LOAD (kgs/lbs) | | MAX. SPEED (KPH/MPH) | RIM WIDTH (Inch) |
|------------------------------|----------------------------|------------|--------------|-------------|------|--------------------|--------|------------------|------------------------------|---------------------|-------------|----------------------|------------------|
| | | | FREE ROLLING | DRIVE WHEEL | | OD(mm) | SW(mm) | | | FREE ROLLING | DRIVE WHEEL | | |
| D203 | 11.00-20 | 18 | - | 710A5 | TT | 1104 | 293 | 20.3 | 145/1000 | - | 6000/13225 | 25/15 | 8.00 |
| D302 | 10.5/80-18 | 10 | 131 | 119 | TT | 885 | 274 | 21.5 | 53/370 | 1950/4300 | 1360/3000 | 40/25 | 9.00 |
| | | 10 | 131 | 119 | TL | 885 | 274 | 21.5 | 53/370 | 1950/4300 | 1360/3000 | 40/25 | 9.00 |
| | 12.5/80-18 | 12 | 142 | 129 | TT | 965 | 308 | 21.5 | 53/370 | 2650/5840 | 1850/4080 | 40/25 | 9.00 |
| | | 12 | 142 | 129 | TL | 965 | 308 | 21.5 | 53/370 | 2650/5840 | 1850/4080 | 40/25 | 9.00 |
| | | 16 | 148 | 135 | TL | 965 | 308 | 21.5 | 71/490 | 3150/6940 | 2180/4805 | 40/25 | 9.00 |
| D303 | 15.00/55-17 [380/55-17] | 10 | 134 | 122 | TL | 850 | 391 | 24.9 | 38/260 | 2120/4670 | 1500/3305 | 40/25 | 13.00 |
| | | 12 | 138 | 125 | TL | 850 | 391 | 24.9 | 40/280 | 2360/5200 | 1650/3635 | 40/25 | 13.00 |
| | 10.5/80-18EG | 10 | 123 | 119 | TL | 885 | 274 | 22.0 | 53/370 | 1950/4300 | 1360/3000 | 40/25 | 9.00 |
| | | 16 | - | 146 | TL | 885 | 274 | 22.0 | 85/585 | 4290/9455 | 3000/6610 | 40/25 | 9.00 |
| | 12.5/80-18EG | 12 | 142 | 129 | TT | 965 | 308 | 26.8 | 53/370 | 2650/5840 | 1850/4080 | 40/25 | 9.00 |
| | | 12 | 142 | 129 | TL | 965 | 308 | 26.8 | 53/370 | 2650/5840 | 1850/4080 | 40/25 | 9.00 |
| | 405/70-24 | 14 | - | 152 | TL | 1176 | 418 | 33.6 | 70/480 | - | 3550/7825 | 50/30 | 14.00 |
| 16.00/70-20EG [405/70-20] | 14 | 154 | 142 | TL | 1075 | 418 | 30.1 | 51/350 | 3750/8265 | 2650/5840 | 40/25 | 14.00 | |
| D309 | 10.00-20 | 16 | - | 164 | TT | 1075 | 278 | 15.3 | 130/900 | - | 5000/11020 | 25/15 | 7.50 |
| D403 | 10.00/75-15.3 | 8 | 119 | 106 | TT | 760 | 264 | 20.1 | 45/310 | 1360/3000 | 950/2095 | 40/25 | 9.00 |
| | | 8 | 119 | 106 | TL | 760 | 264 | 20.1 | 45/310 | 1360/3000 | 950/2095 | 40/25 | 9.00 |
| | | 10 | 123 | 111 | TL | 760 | 264 | 20.1 | 57/400 | 1550/3415 | 1090/2400 | 40/25 | 9.00 |
| | 11.5/80-15.3 | 8 | 126 | 114 | TT | 845 | 290 | 22.0 | 39/270 | 1700/3745 | 1180/2600 | 40/25 | 9.00 |
| | | 8 | 126 | 114 | TL | 845 | 290 | 22.0 | 39/270 | 1700/3745 | 1180/2600 | 40/25 | 9.00 |
| | | 10 | 131 | 119 | TL | 845 | 290 | 22.0 | 49/340 | 1950/4300 | 1360/3000 | 40/25 | 9.00 |
| | 405/70-20 | 14 | 154 | 142 | TL | 1075 | 418 | 26.0 | 51/350 | 3750/8265 | 2650/5840 | 40/25 | 14.00 |