

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rządowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
230/95R32 128D 143A2 Performer 95	230	1254	592	3858	W8	W7

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		1950	2090	2230	2385	2560	2725	2875	3060
10	1735	1895	2040	2200	2385	2560	2725		
25	1355	1485	1595	1725	1865	2005	2135		
30	1315	1440	1550	1675	1810	1945	2070		
40	1255	1370	1475	1595	1725	1850	1975		
50	1205	1315	1415	1530	1655	1775	1890		
65	1145	1255	1350	1455	1575	1690	1800		

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.