

PERFORMER 85-90-95



- Wąskie opony do opryskiwaczy i upraw rządowych
- Wysoka nośność
- Wyjątkowe osiągi na drodze
- Doskonała trakcja i samooczyszczanie się
- Długa żywotność

Wymiary opony

Rozmiar opony	SW	OD	SLR	RC	Zatwierdzona felga	Dopuszczalna felga
230/95R44 134D 148A2 Performer 95	238	1556	736	4791	W8	W7

Tabela Obciążenia i Ciśnień

Prędkość (km/h)	Maks. obciążenie opony(kg) - Ciśnienie w oponie (bar)								
	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0
10*		2310	2475	2650	2820	3030	3225	3420	3605
10	2015	2205	2370	2600	2820	2990	3150		
25	1610	1760	1895	2075	2250	2385	2515		
30	1560	1710	1835	2015	2185	2315	2440		
40	1485	1625	1750	1920	2080	2205	2325		
50	1425	1560	1680	1840	1995	2115	2230		
65	1360	1485	1595	1750	1900	2015	2120		

(*): Cyclic Application (see note)

Note:

- * Cyclic tyre bonus loads are permitted for traction wheels in cyclic loading operations involving minimal torque and wide fluctuation in weight carried.
- * Vehicles must be unloaded before transport outside the field.
- * Maximum load may not be carried for more than 1.5 km before unloading operation begins.
- * Maximum load per tyre includes all possible field and vehicle/usage variations.
- * For hillside operations over 11° (20%) slope, no cyclic bonus load is allowed.
- * Basic inflation pressure must be increased as per tables.